



YDROCHROMA

READY FOR USE ADHESIVE MATERIAL

GENERAL CHARACTERISTICS

YDROCHROMA is a ready for use adhesive material. It is suitable for roofs of bathrooms, kitchens, bedrooms and in general interior use. It can be used on lime surfaces, **but not surfaces painted with emulsion paint**. Permits the surface to “**breath**” to avoid problems with condensed moisture on the roofs. Easy to work with.

TECHNICAL CHARACTERISTICS

- Texture** : Flat.
- Specific gravity** : 1,57 – 1,60 kg/lt.
- Covering power** : 5-7 m²/lt per layer depending on the surface.
- Dilution** : 10-20% on volume with water.
- VOC class** : “Interior mat coatings for walls and ceilings”. Type WB. VOC limit = 30gr/lt. Max VOC of product ready for use = 10gr/lt. It fulfills the requirements of E.C. legislation after 2011. VOC: organic volatile compounds with boiling point < 250°C.
- Drying** : Dry to touch in ½ - 1 hour. The paint adopts full resistance in washing 3-4 weeks after application.
- Recoatibility** : 4 – 6 hours. These times could elongate under cold and wet weather conditions.
- Color shades** : White.

PACKING: 3lt & 9lt.

APPLICATION EQUIPMENT: Brush, roller or thick brush.

SURFACE PREPARATION

Clean the surface of dust, oil, cropped paints, and dampness.

APPLICATION

Stir well before use. Apply two coats **YDROCHROMA**.

CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot or in the paint launder. Strain well your tools from paint back to the pot and clean immediately with water and soap.

APPLICATION CONDITIONS

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality.

STORAGE CONDITIONS

Close well after use. Store in a cool place. Protect from freezing and sun exposure.

SAFETY INSTRUCTIONS

- Keep out of the reach of children.

LABELLING

YDROCHROMA needs no danger symbols according to legislation.