



SMALTOXYL TEAK OIL

PROTECTIVE OIL for TEAK & HARD WOODS

GENERAL CHARACTERISTICS

Smaltoxyl TEAK OIL is special modified oil combined with water repellant wax used for the maintaining and refreshing of hard woods like TEAK, mahogany, iroko and other exotic woods. It replaces lost natural oils of hard woods due to weathering and protects from water, sunlight, salts, stains and greases. Suitable for interior and exterior surfaces. Ideal for garden furniture and decks from hard woods. Very good brush ability and leveling. It penetrates and does not develop film. The product does not contain biocides.

TECHNICAL CHARACTERISTICS

- Specific Gravity** : 0,80-0,82 kg/lit
- Covering power** : 15-17 m²/lit per coat, in already well-primed surface.
- Dilution** : Ready for use
- VOC class** : "Interior and exterior minimal build woodstains." Type SB.
VOC limit =700gr/lit. Max VOC of product ready for use=
550 gr/lit. It fulfills the requirements of E.C. legislation after
2011. VOC: organic volatile compounds with boiling point
< 250°C.
- Drying** : Dry to touch in 3 – 4 hours.
- Recoatibility:** : 6-8 hours after application or after first layer's hardening.
Those times will be prolonged in cold and wet weather
conditions.
- Color shades** : Transparent- Colorless.

PACKING: 750ml και 2,5lt.

APPLICATION EQUIPMENT: Brush, cloth.

SURFACE PREPARATION

Clean the surface of dust, oil, cropped varnishes etc. Sandpaper well and remove dust.

APPLICATION

Stir well before use. Apply 1-2 coats Smaltoxyl TEAK OIL. In old non maintained woods apply one more coat. Remove the excess material after 5 minutes from application. For the best maintenance of hard woods apply once a year.

CLEANING EQUIPMENT

While working keep your equipment wet, either in the pot, or in the paint lauder. Strain well your tools from paint back to the pot and clean immediately with thinner Smaltolux WHITE SPIRIT and water and soap.

APPLICATION CONDITIONS

Temperature 8-35 °C and relative humidity lower than 85%. Adverse conditions will delay drying and hardness development properties.

STORAGE CONDITIONS

Close well after use. Store in a cool place. Protect from sun exposure.

SAFETY INSTRUCTIONS

- Keep out of the reach of children.

LABELLING

SMALTOXYL TEAK OIL wood oil needs no hazard symbols according to EC and National legislation.

*** More information in Material Safety Data Sheets (MSDS).**