



SMALTOPLAST EXTRA

ECOLOGICAL FLAT EMULSION PAINT

GENERAL CHARACTERISTICS

Premium quality ecological flat emulsion paint for interior use. Suitable for walls, concrete, gypsum board, plasters. **SMALTOPLAST extra** is low odor, has excellent whiteness, hiding and covering power. Easy to apply with very good leveling. Very good alkali resistance, wash ability and scrub resistance (EN 13300, class 1). Minimized content of hazardous substances. Reduced volatile organic compounds (VOCs).

TECHNICAL CHARACTERISTICS

- Texture** : Mat (EN 13300/<5) with sheen up to 2-3 units at 85°
- Specific gravity** : 1,30 – 1,50 kg/lit, depending on the shade.
- Covering power** : 11 – 13 m² /lit per layer, depending on the surface
- Hiding power** : >10 m²/lit (ISO 6504/1)
- Dilution** : 8 – 15% on volume with water
- VOC class** : “Interior mat coatings for walls and ceilings”. Type WB. VOC limit = 30gr/lit. Max VOC of product ready for use = 9,5gr/lit. VOC: organic volatile compounds with boiling point < 250°C.
- Formaldehyde emissions** : <20 µgr/m³ , 24 hours after paint application (ISO 16000-3, ISO16000-9, CET/TS15516, EN16402)
- Wet Scrub Resistance** : Class 1 (EN 13300 / ISO 11998)
- Drying** : ½ - 1 hour touch free.
- Recoatibility** : Recoatable 3-5 hours after application. These times prolong under cold and wet weather conditions.
- Shades** : White and thousands ecological shades via VECCHRO Tinting system.

PACKING: White: 375ml, 750ml, 3lt, & 10lt
Shades: 1lt, 3lt & 10lt

APPLICATION EQUIPMENT: Brush, roller or airless spray.

SURFACE PREPARATION

Clean the surface of dust, oil, unsound existing paints and dampness. Sandpaper well and prime with 1 coat of **Smaltoplast Universal Primer**. **Dirty surfaces** (damp, nicotine, ink, fungi, graffiti, oil spots etc) should be primed with special primer **SMALTOX hydro**.

APPLICATION

Stir well. Apply 2 coats of **SMALTOPLAST extra**.

Minimization of paint wastage: for a surface of 10 m², 1,6lt of paint is needed for two coats.

Advice! For dark shades, in order to minimize the number of coats, we propose to apply **SMALTOX hydro** or **SMALTOPLAST extra** in grey shade S 1502-Y when applying yellow shades, S 1502-R for reds etc. or a shade with the same hue from a base with better opacity.

CLEANING TOOLS

While working keep your equipment wet, either in the pot or in the paint launder. Strain well your tools from paint back to the pot and clean immediately with water and soap. Avoid washing materials entering into watercourses.

APPLICATION CONDITIONS

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade product's quality.

STORAGE

Store in a cool place, protect from freezing and sun exposure. Close the can well after application to keep in good condition. Recover unused paint for re-use. Reuse of paint can effectively minimize the product's life cycle environmental impact.

LABELLING

SMALTOPLAST extra needs no danger symbols according to EC legislation.

This product has been awarded with the Eco-label, eco criteria 312/2014/EE product category "indoor & outdoor paints and varnishes".



Better for the environment ...

- Minimized content of hazardous substances
- Reduced volatile organic compounds (VOCs): 9,5gr/lit
- Good performance for indoor use

... better for you.