



## VINYFLEX EMULSION

### FLAT EMULSION PAINT

#### GENERAL CHARACTERISTICS

Water based emulsion paint. It can be used to paint new or old painted walls and ceilings, plasters and wood, gypsum board and concrete surfaces after their proper preparation. Its' great performance in addition with its low price make VINYFLEX ideal for professionals who ask for economic solution.

#### TECHNICAL CHARACTERISTICS

- Texture** : Flat with sheen up to 6-10 units at 85° .
- Specific gravity** : 1,53 – 1,57 kg/lit (white).
- Covering power** : 10 - 12 m<sup>2</sup>/lit per layer depending on the surface.
- Dilution** : 5 – 10% on volume with water
- VOC class** : “Interior matt coatings for walls and ceilings”. Type WB. VOC limit = 30gr/lit. Max VOC of product ready for use = 20gr/lit. VOC: organic volatile compounds with boiling point < 250°C.
- Drying** : Dry to touch in 1 - 2 hours. The paint adopts full resistance in washing 3-4 weeks after application.
- Recoatibility** : 3–5 hours. These times could elongate under cold and wet weather conditions.
- Color shades** : White.

**PACKING:** 3lt & 9lt.

**APPLICATION EQUIPMENT:** Brush, roller and airless spray.

**SURFACE PREPARATION**

Clean the surface of dust, oil, cropped old paints, dampness etc. Sandpaper well and prime with one coat of Smaltoplast Universal Primer or ACRYLIC PRIMER, while **very dirty surfaces** (damp, nicotine, ink, fungi, graffiti, oil spots etc) should be primed with special primer SMALTOX hydro.

**APPLICATION**

Stir well before use. Apply two coats VINYFLEX emulsion.

**CLEANING EQUIPMENT**

While working keep your equipment wet, either in the pot or in the paint launder. Strain well your tools from paint back to the pot and clean immediately with water and soap.

**APPLICATION CONDITIONS**

Temperature 8-30 °C and relative humidity lower than 80%. Contrary weather conditions may degrade paint's quality.

**STORAGE CONDITIONS**

Close well after use. Store in a cool place. Protect from freezing and sun exposure.

**SAFETY INSTRUCTIONS**

- Keep out of the reach of children.

**LABELLING**

VINYFLEX emulsion needs no danger symbols according to legislation.